

FRAMECAD Homogenous Vinyl Flooring

Homogenous PVC Flooring with Poly-urethane reinforcement and printed decorative top layer

Applications

- Motels and Hotels
- Portacabins and Worker Accommodation
- Exhibition Centres
- Low cost housing

Features & Benefits

- Wide range of colours, patterns and surface finishes available
- Top Surface Finishes Available: Gloss, Matt, Deep Matt
- Durable and wear resistant surface
- No wax or polish required
- High Anti-slip rating

Environmental Info

- Manufactured according to ISO14001:2004 environmental standard

Manufacturing Classification:

- Manufactured under an ISO9001:2001 certified quality management system














Installation:

- Colour matched welding rods available
- For detailed installation instructions, please contact info@framecad.com

SPECIFICATIONS				
	Thickness (mm)	Roll Width (m)	Roll Length (m)	Area per 20' GP
FRAMECAD Homogenous Vinyl Flooring	0.40	2.0	25	34,000
	0.45	2.0	25	30,000
	0.50	2.0	25	28,000
	0.55	2.0	25	26,000
	0.60	2.0	25	24,000
	0.70	2.0	25	20,000
	0.80	2.0	25	18,000
	1.00	2.0	25	14,000
	1.30	2.0	20	10,000
	1.50	2.0	20	8,500

PERFORMANCE		
Reaction to Fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E648-06	Class Bfl-S1 ≥ 8 kw/m ² Pass Type I
Flexibility	EN 435 ASTM F137	< 20mm Pass
Slip Resistance	EN 13893 DIN 51130	Class DS R10
Abrasion Resistance	EN 660-2 ASTM D3384	Wear Group P Pass
Residual Indentation	EN 433 ASTM F970	< 0.1mm Static Load 800 psi
Castor Chair	EN 425	Continuous Use
Light Fastness	EN 20105: B02	> Blue Wool Standard 6
Electrical Behaviour (Body Voltage)	EN 1815	< 2.0kV
Dimensional Stability	EN 434	< 0.4mm
Stain and Chemical Resistance	EN 423	Good Resistance
Thermal Resistance	ISO 8302 (EN 12664)	< 0.00809m ² K/W
Smoke Density	ASTM E 662-05	< 450
Fungi and Bacteria Resistance		Does not favour growth

FRAMECAD Homogenous Vinyl Flooring



FRAMECAD Cladding and Lining is distributed by:
FRAMECAD Building Products
PO Box 1292
Auckland 1140, New Zealand

P +64 9 377 6640
F +64 9 307 7139
E info@framecad.com

Innovation Integration Sustainability

www.framecad.com